

22 oz Blockout Vinyl

22 oz Blockout Vinyl is a durable white flexible substrate readily available in 38", 63", 100" and 10'6" rolls. Tear and fade resistant, 22 oz Blockout Vinyl will withstand all types of weather conditions. It is well suited for double sided printed sign applications and pole banners.

Applications:

Digital Printing

Screen Printing

Properties	Test Method	International	USA
Base Fabric	N/A	Polyester	
Threads	DIN 53853	18x18 per inch	
Yarn	DIN 60001	1000x1000 Denier	
Base Fabric Weight	DIN 53352	180 g/m ²	5 oz/yd ²
Type of Coating	N/A	PVC	
Total Weight	DIN 53352	810 g/m ²	22 oz/yd ²
Width	N/A	0.97m, 1.6m, 2.8m, 3.2m	38", 63", 100", 10'6"
Tensile Strength	DIN 53354	2100x2100 N/5cm	
Tear Strength	DIN 53363	380x380 N/5cm	
Flame Resistance	DIN 75200	Passes	
Low Crack Temperature	DIN 53372	-30°C	-22°F

The above information on physical and chemical characteristics is based on upon tests believed to be reliable. The calvues are intended only as a source of information. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)